

TECHNICAL DATA

QUICK48+
COLLECTION

Plank:
7" x 48" inches

Box: 10 planks (=44 Lb.)- Pallet: 50 boxes (=2200 Lb.)

Product specifications.

Total thickness	EN ISO 24346	4 mm + 1.5 mm
Thickness of the wear layer	EN ISO 24340	0,3 mm / 12 Mil
Total weight	EN ISO 23997	1,86 lb./sqft.
Usage classification	EN ISO 10874	23/32/41

QUICK48+
COLLECTION


Plank

← **7"** →

Test results.

Underfloor heating	EN ISO 12524	suitable – max. 27°C (80°F)/ electrical floor heating systems: max 60 W/m ²
Castor chair	EN ISO 4918	pass
Fire resistance	EN ISO 13501-1	Bfl-s1
Light fastness	EN ISO 105-B02	> 7
Thermal resistance	EN 8302	0,035 m ² K/W
Chemical resistance	EN ISO 26987	OK
Residual indentation	EN ISO 24343-1	<0,1mm
Slip resistance	DIN 51130	R10
	EN ISO 13893	class DS
Sound reduction: impact sound	EN ISO 717-2	20 dB
Reflected walking sound	EPLF draft 021029-3- 2004	33 SONE (57% sound reduction)
Dimensional stability	EN ISO 23999	< 0,15 %
Residential warranty		20 years CLASS 23 -HEAVY RESIDENTIAL
Commercial warranty		NOT APPLICABLE
Formaldehyde	EN ISO 717-1	Carb Phase 2 Compliant
Lock strength	EN ISO 10582	> 4 kN/m

48"



TECHNICAL DATA

QUICK48+
COLLECTION

Underlayment

Material		EVA
Thickness		1.5 mm
Compressive strength	EN 826	117 kPa
Punctual conformability	CEN TS 16354: 12 -2013	0.52mm
Water absorption	EN 12087	0.6%

